

# Continuous Laser Printer

Economical continuous forms laser printing for mid-volume applications.



With a print speed of 60 (A4) ppm at 300dpi and a duty cycle of 300,000 pages per month, the CF60 is perfect for medium volume variable data applications including: mailshots, labels, tickets and tags.

## Key Features

- Print speed reaching 60 ppm at 300 dpi resolution
- Up to 300 000 pages monthly workload
- 3000-sheet stacker on board
- Powerful controller providing special functions
- USB, Ethernet, parallel IEEE 1284 and serial (RS 232/RS 422 )
- SAP and AS/400 compatible
- Various types of built-in barcodes
- Cold Fusing technology at lowest market price
- Optional MICR Support

## Economic Solution

The CF 60 continuous laser is an affordable replacement solution to the line printer application providing the high quality of laser printers while offering a competitive cost of ownership.

In addition, the CF 60 integrates a High-End Controller allowing internal form management, n-time format splitting and SPS-control. All this is supported by a 300x300 dpi resolution which provides a high quality output.

## Maximum performance at minimum cost:

With its Status-Out function that gives notice of each correctly printed page via interface, the CF 60 offers the highest print control for trouble-free continuous printing up to 300,000 pages per month.

The Cold Fusing technology by Xenon Flash Lamp provides printing on thermal-sensitive media and best fixing results, even on thick material. The CF 60 is the first high speed continuous form laser that offers high print quality at an affordable price.

## Secure Printing with "SafePrint" Software

Also available on the Al Khattat CF family, the newly announced SafePrint software manages your print jobs and secures your printing. This powerful software can be used to cluster several printers when very large print jobs need to be run in an unattended environment. The software will automatically split the job to the available printers and monitor every single printed page. If a jam occurs or the printer stops, the software will report the exact information related to the non-printed page. SafePrint can be set-up to automatically back-up the job to one of the available printers and resumes from the very specific page where previous printing stopped.

This new and unique feature provides administrators with a high level of security when printing critical output such as customers' statements.

**globalis**  
international

[www.globalis.com](http://www.globalis.com)

Print technology	LED, OPC, cold fusing by Xenon flash lamp
Print speed	60 pages per minute (A4 landscape)
Engine speed	12.7 m/min
Print resolution	300 x 300 dpi
Duty cycle	300,000 pages/month (based on a using period of 60 months)
Media handling	Length: 7 to 20 in. Width: 6.5 to 16 in. Printable width: 14.6 in. Weight: 60-204 g/m Input tray 1: Push Tractor Output Tray : Stacker
Barcodes	EAN 8, EAN 13, EAN 128, 2/5 3-stroke DATALOGIC, 2/5 3-stroke Matrix Codebar, PDF 417, Jetcaps (HP/SAP), CODE 39, 128 MSI, UPC A, UPC E, Postnet, KIX
Optional Barcodes	USD5, Datamatrix, UPS-Maxicode (more barcodes upon request)
Interface and connectivity	Serial: USB, RS232, RS422 Parallel: IEEE 1284 Parallel bi-directional, LAN: Ethernet 10/100 base ,T
Emulations	Microplex Idol, HP PCL 5e, Epson FX-80, IBM Proprinter, Diablo 630, TIFF, ZPL, micro-Postscript
Optional emulations	Printronix IGP, PGL, EPL, DatamaxZPLII, Magnum Code V, Kyocera Prescribe, Express
Memory	RAM: 64 MB, Flash: 16 MB
Functions	Internal barcodes generation Intelligent form management : up 12MB Flash for forms and fonts inside the printer Format splitting : in several subformats by command
Options	MICR Support
Physical	Dimensions (w x d x h): 805 x 850 x 1250 mm
Operating environment	Temperature: 10° to 30° C; Humidity: 30-80% non-condensing Acoustics: <55 dBA Voltage: 100 V to 230 V ; Frequency: 50Hz
Warranty	Standard one-year



[www.globalis.com](http://www.globalis.com)

The information contained in this document is subject to change without notice. All company and product names mentioned herein are trademarks or registered trademarks of their respective owners.

Copyright © 2012 Globalis International

ENBROCH-SEP10



## Contact Information

**Canada** 2345 Michelin, Suite 210 - Laval, Québec, Canada H7L 5B9 Tel.: (450) 686-9981 | Fax: (450) 686-9962 | [info-canada@globalis.com](mailto:info-canada@globalis.com)

**Gulf, Pakistan & CIS** Al-Khaleej Bldg., Office 307, Zabeel Road - P.O. Box: 52460, Dubai, U.A.E. - Tel.: (971-4) 334-6700 | Fax: (971-4) 334-6912 | [info-dubai@globalis.com](mailto:info-dubai@globalis.com)

**Egypt** Nasr City, Cairo 40 Alef of Samir Abdel Raouf Street (Ext. of Makram Abaid) - Floor No. 9 - Flat No. 91 | Floor No.10 - Flat No. 101 - Tel. : (02) 22 73 53 38 – (02) 22 70 28 54 Fax: (02) 22 70 28 54 [info-egypt@globalis.com](mailto:info-egypt@globalis.com)

**Saudi Arabia** Riyadh - Olaya Street | behind Al Moussa Building P.O. Box: 55736 Riyadh 11544 - Tel.: (966-1) 2150122 | Fax: (966-1) 2150664 | [info-saudi@globalis.com](mailto:info-saudi@globalis.com)

**Levant, Iran, Maghreb & Turkey** Garden Tower, Office 9A, Antelias, Beirut - Lebanon Tel.: (961) 4 41 42 48 | Fax: (961) 4 41 48 42 | [info-maghreb@globalis.com](mailto:info-maghreb@globalis.com) - [info-beirut@globalis.com](mailto:info-beirut@globalis.com)

**Central America** Calle Antigua a San Antonio Abad, Pasaje Carolina #20 - San Salvador, El Salvador, Centro America. Tel: (503) 2542-0732 - (503) 7696-906 [info-elsalvador@globalis.com](mailto:info-elsalvador@globalis.com)