

>> High speed and High Performance
24 Wire Dot Matrix Printer

Dot Matrix Printers



impact 4550



High speed, high copy capability and heavy duty multifunctional flatbed impact printer, ideal for mission critical environments.

KEY FEATURES

- High speed printing up to 1215 cps
- High copy capability
- Straight paper path route (Flat Bed)
- Up to 1 + 8 copies
- 8 different paper path set-ups available
- APTC and HCPP Functions
- Various interfaces available

Unmatched performance

With full print speeds reaching 1215 cps @ 15 cpi in Draft mode, the Globalis impact 4550 flat-bed printer is a highly suitable solution for saving valuable time at the office.

Speed & flexibility

The Globalis impact 4550 printer provides superior performance with form feed speed of 12" per second continuous feed and has been designed to offer several paper loading inputs available at the same time with options. Depending on the print usage, a maximum of 4 paper paths can be set simultaneously.

Outstanding paper handling

Flat bed printer with straight paper path route provides more accurate line feed and enables paper to be fed more smoothly.

With 8 various paper paths set-ups, the impact 4550 is suitable for any printer setting circumstances. The printer offers enhanced paper handling capability to ensure flexibility and comes with standard features like APTC (Automatic Paper Thickness Control) and HCCP (Host Controlled Paper Path).

globalis
international

www.globalis.com

Bilingual print speed

	10 cpi	12 cpi	15 cpi
Draft	810 cps	972 cps	1215 cps
Enhanced Draft	609 cps	730 cps	913 cps
NLQ	360 cps	432 cps	540 cps
LQ	180 cps	216 cps	270 cps

Character sets

Arabic code sets: ASMO-449/449+, ASMO-708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL, CODAR, NCR ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 348/ 541, CITO, Ameer, Integro 708, UNIX, ASMO/French, French/ASMO, ADOS-708/709/710/711/720/128/864/96, Mussaed Arabi,

Arabic Windows 1256, Ameer, User-defined

Operating mode support

8-bit Arabic with neutrals, GLCCs, & GLCCs balancing
7-bit Arabic with GLCCs, GLCCs balancing, & escape sequences

Fonts

Bitmap: Draft 12, HSD 12, Courier 10, Prestige, Boldface PS, Elite12, Compressed, OCR-A 10, OCR-B 10, Correspondence 10, PICA Scalable: Courier, Nimbus Sans, Timless (Normal, Bold, Italic)

Barcodes

Code 128, Code 3 of 9, UPC/A, UPC/A with check character, EAN-8, EAN-13, Codabar (NW7), EAN13, EAN8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5

Print characteristics

Vertical spacing: 1, 2, 3, 4, 5, 6, 7 and 8 lpi
Horizontal spacing: 2.5, 3, 5, 6, 10, 12, 15, 17, 18, 20 cpi and proportional
Print line length: 136 columns @ 10 cpi

Resolution

360 x 360 dpi

Print modes

Condensed, double width/height, quadruple w/h, shadow, italic, bold

Paper handling

Continuous form: Push tractor - Front in, Rear out; Rear in, Front out
Cut Sheet: Front in, Front out; Front in, Rear out; Rear in, Front out; Rear in, Rear out
Paper width: - Cut Sheet: Width 55~420 mm (2.2~16.5 inch)
Length 70~297 mm (2.76~11.69 inch), 70~240mm (2.76~16.5 inch) for Large Cut Sheet Table
- Continuous Form: Width 102~420 mm (4.0~16.5 inch)
Length Over 102 mm (Over 4.0 inch), Over 127 mm (Over 5.0 inch) for Rear Tractor
Max. Paper Thickness: 0.65mm (0.256")
Number of copies: Original plus 7; at High Copy mode: original + 8

Optional accessories

Cut sheet feeder
LAN Card
Rear Stacker
Small cut sheet table (should be installed for Front CSF)
Large Cut Sheet Table (should be installed for Front CSF)
Tractor (Common to Rear and Front)

Automating functions

Paper path switch, Auto Paper Thickness control, paper skew detection for cut sheet

Emulation

Epson ESC/P2, IBM® Proprinter XL24E, Fujitsu DPL24C PLUS

Interface and connectivity

Parallel port: IEEE Nibble Mode
Serial port: RS-232C 25pin
USB: Ver 1.1 (TYPE B)
Ethernet : 10 Base-T, 100 Base-TX, TCP/IP Protocol (Optional card needed)

Model

Parallel + USB Model (LAN Upgradeable)
Parallel + RS232C Model

Input data buffer

128 KB

Throughput

450 pages per hour

Drivers

Plug & Play (Microsoft Windows Driver)

Reliability

MTBF: 20,000 hours @25% duty cycle

Consumables

Type: Black ribbon cartridge; Life: 18 million characters

Print head life

400 million characters (400 million strokes)

Physical

Dimensions (w x d x h): 600 x 350 x 290 mm (23.62 x 13.78 x 11.42 inch)
Weight: ~22 kg (48 lbs)

Operating environment

Temperature: Operating: 5⁰ to 38⁰ C; Humidity: 20-80%; Acoustics: 56dBA
Voltage: 110 ~ 120 V / 220 ~ 240 V; Frequency: 50 to 60 Hz; Power Consumption: 120W / 14W (waiting)

Warranty

Standard one year



Contact Information

Canada 2345 Michelin, Suite 210 - Laval, Québec, Canada H7L 5B9 Tel.: (450) 686-9981 | Fax: (450) 686-9962 | info-canada@globalis.com

Gulf, Pakistan & CIS Al-Khaleej Bldg., Office 307, Zabeel Road - P.O. Box: 52460, Dubai, U.A.E. - Tel.: (971-4) 334-6700 | Fax: (971-4) 334-6912 | info-dubai@globalis.com

Egypt Nasr City, Cairo 40 Alef of Samir Abdel Raouf Street (Ext. of Makram Abaid) - Floor No. 9 - Flat No. 91 | Floor No.10 - Flat No. 101 - Tel. : (02) 22 73 53 38 – (02) 22 70 28 54 Fax: (02) 22 70 28 54 info-egypt@globalis.com

Saudi Arabia Riyadh - Olaya Street | behind Al Moussa Building P.O. Box: 55736 Riyadh 11544 - Tel.: (966-1) 2150122 | Fax: (966-1) 2150664 | info-saudi@globalis.com

Levant, Iran, Maghreb & Turkey Garden Tower, Office 9A, Antelias, Beirut - Lebanon Tel.: (961) 4 41 42 48 | Fax: (961) 4 41 48 42 | info-maghreb@globalis.com - info-beirut@globalis.com

Central America Calle Antigua a San Antonio Abad, Pasaje Carolina #20 - San Salvador, El Salvador, Centro America. Tel: (503) 2542-0732 - (503) 7696-906 info-elsalvador@globalis.com