





impact 3336

Reliable compact printer that delivers high print quality at speed reaching 540 cps. Globalis 3336 provides advanced paper handling to support the largest variety of papers. It is ideally suited for business and industrial working environments where reliability, speed and quality are critical factors.

KEY FEATURES

- Print speed up to 540 cps
- 300 million strokes per wire print head life
- Up to 360 x 360 dpi print resolution
- 6 million characters ribbon life
- Up to 6 copies
- Up to 128 KB input buffer
- 20.000 hours MTBF
- Advanced paper handling for trouble-free use of continuous forms
- Standard Parallel and USB interfaces and optional serial interface
- Integrated LAN (option)
- Ideally designed for Continuous forms, Adhesive slip, Multicopy parts.
- Available with built-in Arabization for full Arabic standard support

Reliable mechanism

The impact 3336 features an advanced tractor mechansim that allows flexible paper manipulation from: front in/top out, rear in/top out and from bottom in/top out. The impact 3336 comes standard with a powerful 24-pin print head that functions on different types of paper using a wide range of fonts, character sets and barcodes.

Outstanding performance

The Impact 3336 printer is designed to offer the best print techniques for a good quality output at a minimum cost. It delivers the same quality output on single sheets as well as on multiple copy forms up to 1+5 copies.





Technical Specifications



impact 3336

Print technology	24-pin, serial impact dot matrix
Bilingual print speed	Max HSD Draft LQ
	540 cps
	12 cpi 435 cps 145 cps
	10 срі 480 срѕ 360 срѕ 120 срѕ
Character sets	Host code sets: ASMO-449/449+, ASMO- 708/708+, ARCII, ASCII, DEC/8/ASMO, Al-Arabi, IBM APC, XBASIC, CODAR-UFD, ICL
	CODAR, ICL ASMO-708, Cross Range, NCR 64/96, Data General, HP Arabic-8, HP Enhanced, Comterm 341/348/541, Integro 70
	UNIX, ASMO/French, French/ASMO, User-defined
	PC code sets: AD0S-708/709/710/711/720/128 864/96, Mussaed Arabi, Arabic Windows 1256, IBM437, IBM851, IBM864
Operating mode support	8-bit Arabic with neutrals, GLCCs, & GLCCs balancing
	7-bit Arabic with GLCCs, GLCCs balancing, & escape sequences
Arabic fonts	Naskh Draft, Naskh NLQ
Latin fonts	Draft, Roman, Sans Serif, OCR-A, OCR-B, etc.
Bar codes	8 types including EAN-13, Code 39, Code 128
Print characteristics	Width: Cut Sheet: 148 - 420 mm
	Continuous paper: 101-406 mm
	Length (cut sheet): up to 364 mm
	Thickness: 0.065 to 0.52 mm
Number of copies	Original + 5
Print resolution	360 x 360 dpi
Number of columns	136 col.
Paper Insertion	Cut Sheet: Front in/Top Out
	Rear in/Top Out
	Continous: Front in/Top Out
	Rear in/Top Out
	Bottom in/Top out
Emulation	Epson ESC P, OKI
Interface and connectivity	Parallel and USB interface (standard)
	Optional: Serial
	Optional: Integrated Ethernet LAN 10/100 Base T
Input data buffer	Up to 128 Kb
Consumables	Type: Black ribbon cartridge
	Life: 6 million characters
Print head life	300 million strokes per wire
MTBF	20,000 hours
Physical	Dimensions (w x d x h): 623 x 395 x 173 mm
	Weight: 13 kg
Operating environment	Temperature: Operating: 5° to 35° C; Storage: -20° to 60°; Humidity: 20% to 80% (operating); Consumptions: 15W to 75W;
	Ac oustics: 56 dBa; Voltage: 220 v, 165 to 264 VAC; Frequency: 49.5 to 60 Hz;
Warranty	Standard one-year







www.globalis.com

Head Office Montreal, canada | Tel.: (514) 855-4994 | Fax: (514) 855-0541 | E-mail: info@globalis.com

Egypt Cairo

Levant & Maghreb Beirut

Gulf, Pakistan & Iran Dubai | Tel.: (971-4) 334-6700 | Fax: (971-4) 334-6912 | E-mail: info-dubai@globalis.com

Syria Damascus

Tel./Fax: (963-11) 44675240 Cel.: (963-944) 71 67 27 E-mail: info-syria@globalis.com

